



Bisnode Liidi AJAX tracking

Version 2.0

16.02.2010

## BISNODE LIIDI AJAX DOCUMENTATION

The basic Bisnode Liidi tracking works by informing Bisnode's servers about the activity every time a new HTML page is rendered in the browser. For web sites using AJAX or Flash where actions are carried out with the same page loaded in the browser all the time, some additional setup is required to get the data tracked. The tracking Javascript should be executed manually every time the page visitor performs an action that should be registered.

First, the data to track should be set, using `piwikTracker.setCustomUrl` and/or `piwikTracker.setDocumentTitle`. When the data has been set up, it is then sent to the tracker using `piwikTracker.trackPageView`.

`piwikTracker.setCustomUrl` takes one argument, the URL that should be displayed in the lead email for the pageview. If no URL has been set, the URL of the original html page is used.

`piwikTracker.setDocumentTitle` takes one argument, the page title that should be displayed in the lead email. If no title is set, the contents of the title-tag of the original html page is used.

### Example with Javascript

```
function contactsClicked(event) {
  piwikTracker.setCustomUrl('http://www.site.fi/contacts');
  piwikTracker.setDocumentTitle('Contacts');
  piwikTracker.trackPageView();
  // Continue displaying the information box with contact information...
  ...
}
```